

**JDYX2.E482688**
Fuses, Supplemental - ComponentPage Bottom**Fuses, Supplemental - Component**See General Information for Fuses, Supplemental - Component**SHANGHAI ECUBE-TECH ELECTRONICS TECHNOLOGY CO LTD**

E482688

4399 Wusi Rd Haiwan Town Fengxian District

200000 Shanghai, CHINA

Supplemental fuses: pigtail leads

Cat. No.	Size mm(in)	Amps (A)	Volts (V)	Interrupting Rating (A)
F3A	4.0 x 12.0 (0.16 x 0.47)	0.25 - 10	125Vac	50
		0.25 - 10	250Vac	50
F3B	4.0 x 12.0 (0.16 x 0.47)	0.25 - 10	125Vac	50
		0.25 - 10	250Vac	50
T3A	4.0 x 12.0 (0.16 x 0.47)	0.25 - 10	125Vac	50
		0.25 - 10	250Vac	50
T3B	4.0 x 12.0 (0.16 x 0.47)	0.25 - 10	125Vac	50
		0.25 - 10	250Vac	50

Supplemental micro fuses

Cat. No.	Size mm(in)	Amps (A)	Volts (V)	Interrupting Rating (A)
F2410A	6.1 x 2.6 x 2.6 (0.24 x 0.10 x 0.10)	0.05 - 15	125Vac	100
F2410B	6.1 x 2.6 x 2.6 (0.24 x 0.10 x 0.10)	0.05 - 10	250Vac	50
F2410C	6.1 x 2.6 x 2.6 (0.24 x 0.10 x 0.10)	0.05 - 10	300Vac	50
T2410A	6.1 x 2.6 x 2.6 (0.24 x 0.10 x 0.10)	0.05 - 15	125Vac	100
T2410B	6.1 x 2.6 x 2.6 (0.24 x 0.10 x 0.10)	0.05 - 10	250Vac	50
T2410C	6.1 x 2.6 x 2.6 (0.24 x 0.10 x 0.10)	0.05 - 10	300Vac	50

Supplemental micro fuses: filled-tube

Cat. No.	Size mm(in)	Amps (A)	Volts (V)	Interrupting Rating (A)
PFA	8.4 x 7.7 x 4.0 (0.33 x 0.30 x 0.16)	0.1 - 6.3	250Vac	50
PFB	8.4 x 7.7 x 4.0	0.1 - 6.3	350Vac	50

	(0.33 x 0.30 x 0.16)			
PTA	8.4 x 7.7 x 4.0 (0.33 x 0.30 x 0.16)	0.1 - 6.3	250Vac	50
PTB	8.4 x 7.7 x 4.0 (0.33 x 0.30 x 0.16)	0.1 - 6.3	350Vac	50

Marking: Company name and model designation.

Last Updated on 2016-03-03

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

◆ 2016 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2016 UL LLC".