

Standard Structure (or Customized):



Electrical Specifications

Part No.	Varistor Voltage	Maximum Allowable Voltage		Maximum Clamping Voltage	Withstanding Surge Current 8/20μs		Energy
	V1mA(V)	AC(V)	DC(V)	Vc(500A)	1times(KA)	2times(KA)	10/1000μs(J)
(W)/CA***-53D431K	430	275	350	710	70	35	675
(W)/CA***-53D471K	470	300	385	775	70	35	730
(W)/CA***-53D511K	510	320	415	845	70	35	810
(W)/CA***-53D561K	560	345	460	925	70	35	910
(W)/CA***-53D621K	620	385	505	1025	70	35	1000
(W)/CA***-53D681K	680	420	560	1120	70	35	1140
(W)/CA***-53D751K	750	460	615	1240	70	35	1200
(W)/CA***-53D821K	820	510	670	1355	70	35	1240
(W)/CA***-53D911K	910	550	745	1500	70	35	1270

CONTACT INFORMATION

Shanghai Ecube-Tech Electronics Technology Co., Ltd.

上海赫品电子科技有限公司

Email: Marketing@ecube-tech.com

Tel:+86 21 50723288

Fax:400 8892 163 Ext. 324988

Address: No.245, Jinan Road, Huangpu Area, Shanghai, 200021, China

Website: www.ecube-tech.com