


Naming Rule:

T	3	B	L	-	xxB
1	2	3	4		5

1. Time-lag
2. Fuselink 4*12mm
3. A: Ceramic tube B: Glass tube
4. W: Without lead L: Leded
5. Rated Current&Voltage
(e.g.:0315A=315mA/125V;
6300B=6.3A/250V)

Structure:(Unit:mm)



NO.	Position	Material
①	End Cap	Nickel plated brass
②	Inner Cap	Nickel plated brass
③	Glass Tube	Glass
④	Fuse Element	Alloy
⑤	Lead Wire	Tinned copper wire

Operating Characteristics:

% of Ampere Rating(In)	Blowing Time
150%	1 hour Min
210%	2 min Max
275%	400 ms~10 s
400%	150 ms~3 s
1000%	20 ms~150 ms

Product Characteristics:

- ✧ **Lead Pull Strength:** 5N for 1 Minute
- ✧ **Solder ability:** Wave : 260℃, ≤10s; Soldering Iron: 350℃, ≤3s.


Electrical Characteristics

- ✧ **Test Condition**
All electrical test is to be conducted with the ambient air at a temperature of $25 \pm 5^\circ\text{C}$.
- ✧ **Interrupting Rating:**
Breaking Capacity: 50A @ 250V/125V AC.
The insulation resistance value of fuse is greater than $0.1 \text{ M } \Omega$ after breaking capacity testing.
- ✧ **Rising Temperature Test:**
Under the ambient temperature of $25 \pm 5^\circ\text{C}$, through 1.5 times the rated current for 15 minutes, then every 15 minutes, add an increase of 0.1 times the rated current. When operates, the temperature rise in any part of fuse should not exceed 135°C .

Electrical Specifications: *=L/W

Part No.	Ampere Rating(A)	Voltage Rating	Maximum Voltage Drop (mV)	Maximum Sustained Power Dissipation (mW)
T3B*-0250B	0.25	250V	240	220
T3B*-0315B	0.315	250V	220	250
T3B*-0400B	0.4	250V	200	280
T3B*-0500B	0.5	250V	190	310
T3B*-0630B	0.63	250V	180	360
T3B*-0800B	0.8	250V	160	430
T3B*-1000B	1.0	250V	140	500
T3B*-1250B	1.25	250V	130	600
T3B*-1600B	1.6	250V	120	730
T3B*-2000B	2.0	250V	100	870
T3B*-2500B	2.5	250V	100	1000
T3B*-3150B	3.15	250V	100	1200
T3B*-4000B	4.0	250V	100	1400
T3B*-5000B	5.0	250V	100	1680
T3B*-6300B	6.3	250V	100	2000
T3B*-8000B	8.0	250V	100	2500
T3B*-10000B	10.0	250V	100	3000

Average Time Current Curves



CONTACT INFORMATION

Shanghai Ecube-Tech Electronics Technology Co., Ltd.

上海赫品电子科技有限公司

Email: Marketing@ecube-tech.com

Tel: +86 21 50723288

Fax: 400 8892 163 Ext. 324988

Address: No.245, Jinan Road, Huangpu Area, Shanghai, 200021, China

Website: www.ecube-tech.com