

Standard Structure (or Customized):



Electrical Specifications

Part No.	Varistor Voltage	Maximum Allowable Voltage		Maximum Clamping Voltage	Withstanding Surge Current 8/20μs		Energy
	V1mA	AC	DC	Vc	1times	2times	10/1000μs
	(V)	(V)	(V)	150A	(KA)	(KA)	(J)
(W)/CA***-25D201K	200	130	170	340	20	10	150
(W)/CA***-25D221K	220	140	180	360	20	10	175
(W)/CA***-25D241K	240	150	200	390	20	10	185
(W)/CA***-25D271K	270	175	225	445	20	10	210
(W)/CA***-25D301K	300	195	250	495	20	10	230
(W)/CA***-25D331K	330	210	270	545	20	10	235
(W)/CA***-25D361K	360	230	300	595	20	10	245
(W)/CA***-25D391K	390	250	320	650	20	10	255
(W)/CA***-25D431K	430	275	350	710	20	10	275
(W)/CA***-25D471K	470	300	385	775	20	10	300
(W)/CA***-25D511K	510	320	415	845	20	10	330
(W)/CA***-25D561K	560	345	460	925	20	10	375
(W)/CA***-25D621K	620	385	505	1025	20	10	420
(W)/CA***-25D681K	680	420	560	1120	20	10	440
(W)/CA***-25D751K	750	460	615	1240	20	10	485
(W)/CA***-25D821K	820	510	670	1355	20	10	505
(W)/CA***-25D911K	910	550	745	1500	20	10	520
(W)/CA***-25D102K	1000	625	825	1650	20	10	540

Part No. Instruction

Name Rule: e.g. WB003-34S621KD2

W		B003		34		S		621		K		D2	
Coating Condition		Outline		Dimension		D	Round	Varistor Voltage		Varistor Voltage Tolerance		Paralleled Chips	
W	Welding	B003		34: 34mm as length of one side or as diameter		S	Square	180=18*10 ⁰ 471=47*10 ¹		K	±10%	D2=2 Chips D3=3 Chips D4=4 Chips	
C	Coating	D001				E	Customized	182=18*10 ²		L	±15%		

CONTACT INFORMATION

Shanghai Ecube-Tech Electronics Technology Co., Ltd.

上海赫品电子科技有限公司

Email: Marketing@ecube-tech.com

Tel:+86 21 50723288

Fax:400 8892 163 Ext. 324988

Address: No.245, Jinan Road, Huangpu Area, Shanghai, 200021, China

Website: www.ecube-tech.com