

1. WA/CA Series

Standard Structure (or Customized):

					
WA001	WA002	CA003	CA004	CA005	CA006

Electrical Specifications

Part No.	Varistor Voltage	Maximum Allowable Voltage		Maximum Clamping Voltage	Withstanding Surge Current 8/20μs		Energy
	V1mA	AC	DC	Vc	1times	2times	10/1000μs
	(V)	(V)	(V)	300A	(KA)	(KA)	(J)
(W)/CA***-34S201K	200	130	170	340	40	20	390
(W)/CA***-34S221K	220	140	180	360	40	20	425
(W)/CA***-34S241K	240	150	200	390	40	20	450
(W)/CA***-34S271K	270	175	225	445	40	20	480
(W)/CA***-34S301K	300	195	250	495	40	20	510
(W)/CA***-34S331K	330	210	270	545	40	20	540
(W)/CA***-34S361K	360	230	300	595	40	20	575
(W)/CA***-34S391K	390	250	320	650	40	20	615
(W)/CA***-34S431K	430	275	350	710	40	20	675
(W)/CA***-34S471K	470	300	385	775	40	20	730
(W)/CA***-34S511K	510	320	415	845	40	20	810
(W)/CA***-34S561K	560	345	460	925	40	20	910
(W)/CA***-34S621K	620	385	505	1025	40	20	1000
(W)/CA***-34S681K	680	420	560	1120	40	20	1140
(W)/CA***-34S751K	750	460	615	1240	40	20	1200
(W)/CA***-34S821K	820	510	670	1355	40	20	1240
(W)/CA***-34S911K	910	550	745	1500	40	20	1270
(W)/CA***-34S102K	1000	625	825	1650	40	20	1320

2. WB/CB Series

Standard Structure (or Customized):

				
WB001	WB002	CB003	CB004	CB005

Electrical Specifications

Part No.	Varistor Voltage	Maximum Allowable Voltage		Maximum Clamping Voltage	Withstanding Surge Current 8/20μs		Energy
	V1mA	AC	DC	Vc	1times	2times	2ms
	(V)	(V)	(V)	500A	(KA)	(KA)	(J)
(W)/CB***-34S431KD2	430	275	350	710	80	40	1000
(W)/CB***-34S471KD2	470	300	385	775	80	40	1160
(W)/CB***-34S511KD2	510	320	415	845	80	40	1200
(W)/CB***-34S561KD2	560	345	460	925	80	40	1400
(W)/CB***-34S621KD2	620	385	505	1025	80	40	1600
(W)/CB***-34S681KD2	680	420	560	1120	80	40	1800
(W)/CB***-34S751KD2	750	460	615	1240	80	40	1900
(W)/CB***-34S821KD2	820	510	670	1355	80	40	1980
(W)/CB***-34S911KD2	910	550	745	1500	80	40	2000

3. WC/CC Series

Standard Structure (or Customized):



Electrical Specifications

Part No.	Varistor Voltage	Maximum Allowable Voltage		Maximum Clamping Voltage	Withstanding Surge Current 8/20μs		Energy
	V1mA(V)	AC(V)	DC(V)	Vc(800A)	1times(KA)	2times(KA)	2ms(J)
(W)/CC***-34S431KD3	430	275	350	710	100	50	1600
(W)/CC***-34S511KD3	510	320	415	845	100	50	1900
(W)/CC***-34S621KD3	620	385	505	1025	100	50	2400
(W)/CC***-34S681KD3	680	420	560	1120	100	50	2700

4. WD/CD Series

Standard Structure (or Customized):



Electrical Specifications

Part No.	Varistor Voltage	Maximum Allowable Voltage		Maximum Clamping Voltage	Withstanding Surge Current 8/20μs		Energy
	V1mA(V)	AC(V)	DC(V)	Vc(1000A)	1times(KA)	2times(KA)	2ms(J)
(W)/CD***-34S431KD4	430	275	350	710	120	60	2100
W)/CD***-34S511KD4	510	320	415	845	120	60	2500
W)/CD***-34S621KD4	620	385	505	1025	120	60	3200
W)/CD***-34S681KD4	680	420	560	1120	120	60	3600

Part No. Instruction

Name Rule: e.g. WB003-34S621KD2

W		B003		34		S		621		K		D2	
Coating Condition		Outline		Dimension		D	Round	Varistor Voltage		Varistor Voltage Tolerance		Paralleled Chips	
W	Welding	B003		34: 34mm as length of one side or as diameter		S	Square	180=18*10 ⁰ 471=47*10 ¹		K	±10%	D2=2 Chips D3=3 Chips D4=4 Chips	
C	Coating	D001				E	Customized	182=18*10 ²		L	±15%		

CONTACT INFORMATION

Shanghai Ecube-Tech Electronics Technology Co., Ltd.

上海赫品电子科技有限公司

Email: Marketing@ecube-tech.com

Tel:+86 21 50723288

Fax:400 8892 163 Ext. 324988

Address: No.245, Jinan Road, Huangpu Area, Shanghai, 200021, China

Website: www.ecube-tech.com